

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 1 430 861 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
23.06.2004 Bulletin 2004/26

(51) Int Cl.7: **A61F 13/15**, D04H 1/00,  
D04H 3/00

(21) Application number: **02258797.6**

(22) Date of filing: **19.12.2002**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR**  
**IE IT LI LU MC NL PT SE SI SK TR**  
Designated Extension States:  
**AL LT LV MK RO**

(72) Inventor: **Huang, Chen-Cheng**  
**Taipei City (TW)**


(74) Representative: **Moir, Michael Christopher et al**  
**Mathys & Squire**  
**100 Gray's Inn Road**  
**London WC1X 8AL (GB)**

(71) Applicant: **Huang, Chen-Cheng**  
**Taipei City (TW)**

(54) **Perforated plastically deformable sheet and method for making the same**

(57) A perforated plastically deformable sheet (3) includes a plastically deformable sheet (4) with top and bottom surfaces (41, 42). The plastically deformable sheet (4) is formed with a plurality of recesses (44) and

a plurality of capillaries (40), each of which extends from a respective one of the recesses (44). Each of the recesses (44) has a cross-section greater than that of the respective one of the capillaries (40).



**FIG. 4**

**EP 1 430 861 A1**

## Description

[0001] This invention relates to a perforated plastically deformable sheet and a method for making the same, more particularly to a perforated plastically deformable sheet with a plurality of recesses and a plurality of capillary units and to a method for forming the recesses and the capillary units in the perforated plastically deformable sheet.

[0002] Figs. 1 and 2 illustrate a conventional perforated plastically deformable sheet 2 that can be used as a top sheet of an absorptive device, such as diapers, bandages, water-retaining agent for agriculture use, and sanitary napkins or can be used as packaging and decorating material. The perforated plastically deformable sheet 2 has opposite top and bottom surfaces 21, 22, and is perforated to form a plurality of tapered capillaries 23. Each of the capillaries 23 has a bottom opening 231 spaced apart from the bottom surface 22 in a direction away from the top surface 21 and adapted to be in intimate contact with an absorbent batt (not shown) so that liquid accumulated on the top surface 21 of the plastically deformable sheet 2 can be absorbed by the absorbent batt through the capillaries 23 (a wicking action). Formation of the capillaries 23 is performed by advancing a softened plastically deformable sheet through a vacuum screen drum, which causes the softened plastically deformable sheet to rupture at screen holes in the vacuum screen drum.

[0003] The conventional perforated plastically deformable sheet 2 is disadvantageous in that the height of each of the thus formed capillaries 23 is relatively small and a sufficient distance between the absorbent batt and the top surface 21 cannot be provided to prevent liquid from wetbacking from the absorbent batt to the top surface 21 (which is in contact with the user's skin). Moreover, since prolonged contact with the perforated plastically deformable sheet 2 can irritate the user's skin, there is a need to minimize the contact area of the perforated plastically deformable sheet 2 with the user's skin.

[0004] Therefore, the object of the present invention is to provide a perforated plastically deformable sheet that is capable of overcoming the aforesaid drawbacks of the prior art.

[0005] Another object of the present invention is to provide a method for making the perforated plastically deformable sheet.

[0006] According to one aspect of the present invention, a perforated plastically deformable sheet comprises: a plastically deformable sheet having opposite top and bottom surfaces and formed with a plurality of spaced apart recesses and a plurality of spaced apart capillary units that are vertically and respectively aligned with the recesses. Each of the capillary units includes at least one capillary that has a cross-section less than that of the respective one of the recesses. Each of the recesses is indented from the top surface toward the

bottom surface and is confined by a recess-confining wall that has a peripheral surface extending downwardly from the top surface toward the bottom surface, and a bight surface that extends laterally from the peripheral surface. The capillary of each of the capillary units extends downwardly from the bight surface of the recess-confining wall of the respective one of the recesses in a transverse direction relative to the bight surface, and has a top opening adjoining the respective one of the recesses and a bottom opening opposite to the top opening and spaced apart from the bottom surface in a direction away from the top surface.

[0007] According to another aspect of the present invention, a method for making the perforated plastically deformable sheet comprises the steps of: (a) preparing a plastically deformable sheet; (b) preparing a screen mold including a first screen element and a second screen element connected to and disposed above the first screen element, the first and second screen elements being respectively formed with a plurality of first and second screen holes, each of the second screen holes having a cross-section greater than those of the first screen holes, each of the second screen holes spanning at least one of the first screen holes; (c) heating and softening the plastically deformable sheet and laying the plastically deformable sheet on the second screen element; and (d) applying a negative pressure at one side of the first screen element opposite to the softened plastically deformable sheet in such a manner that the softened plastically deformable sheet is pulled and ruptured at the first screen holes.

[0008] In drawings which illustrate embodiments of the invention,

Fig. 1 is a fragmentary perspective view of a conventional perforated plastically deformable sheet for an absorptive device;

Fig. 2 is a fragmentary sectional view of the perforated plastically deformable sheet of Fig. 1;

Fig. 3 is a fragmentary top view of a preferred embodiment of a perforated plastically deformable sheet according to this invention;

Fig. 4 is a sectional view taken along line IV-IV in Fig. 3;

Fig. 5 is a schematic side view illustrating how the perforated plastically deformable sheet of Fig. 3 is made using a vacuum screen drum of an apparatus according to a method of this invention;

Fig. 6 is a fragmentary perspective view of a screen mold of the vacuum screen drum shown in Fig. 5;

Fig. 7 is a schematic side view of another apparatus for making the perforated plastically deformable sheet according to this invention; and

Fig. 8 is a fragmentary sectional view of a second preferred embodiment of the perforated plastically deformable sheet according to this invention.

[0010] For the sake of brevity, like elements are de-

noted by the same reference numerals throughout the disclosure.

[0011] Figs. 3 and 4 illustrate a first preferred embodiment of a perforated plastically deformable sheet 3 of this invention that can be used as a top sheet of an absorptive device, such as diapers, bandages, water-retaining agent for agriculture use, and sanitary napkins or can be used as packaging and decorating material.

[0012] The perforated plastically deformable sheet 3 includes: a plastically deformable sheet 4 having opposite top and bottom surfaces 41, 42 and formed with a plurality of spaced apart recesses 44 and a plurality of spaced apart capillary units that are vertically and respectively aligned with the recesses 44. Each of the capillary units includes at least one capillary 40 that has a cross-section less than that of the respective one of the recesses 44. Each of the recesses 44 is indented from the top surface 41 toward the bottom surface 42, and is confined by a recess-confining wall 43 that has a peripheral surface 431 extending downwardly from the top surface 41 toward the bottom surface 42, and a bight surface 432 that extends laterally from the peripheral surface 431. The capillary 40 of each of the capillary units extends downwardly from the bight surface 432 of the recess-confining wall 43 of the respective one of the recesses 44 in a transverse direction relative to the bight surface 432, and has a top opening 401 adjoining the respective one of the recesses 44 and a bottom opening 402 opposite to the top opening 401 and spaced apart from the bottom surface 42 in a direction away from the top surface 41.

[0013] In this preferred embodiment, the recesses 44 are hexagonal in shape, are classified into two different sizes, and have a pattern such that each of the larger ones (indicated as reference numeral 100 in Fig. 3) of the recesses 44 is surrounded by a plurality of the smaller ones (indicated as reference numeral 200 in Fig. 3) of the recesses 44. Each of the larger ones 100 of the recesses 44 spans seven capillaries 40 of a respective one of the capillary units. Each of the smaller ones of the recesses 44 spans three capillaries 40 of a respective one of the capillary units.

[0014] The perforated plastically deformable sheet 3 is preferably made from a hydrophobic and non-woven fabric. The non-woven fabric is preferably a fibrous based material which can contain solely a fiber material or a mixture of different fiber materials. Each of the capillaries 40 of the capillary units is tapered from the top opening 401 toward the bottom opening 402.

[0015] Fig. 8 illustrates a second preferred embodiment of the perforated plastically deformable sheet of this invention that has a structure similar to the previous embodiment shown in Fig. 4, except that the perforated plastically deformable sheet 3 of this embodiment includes a top layer 51 of a hydrophilic material and a bottom layer 52 of a hydrophobic material that is adhered to a bottom side of the top layer 51.

[0016] Figs. 5 and 6 illustrate an apparatus 300 for

making the perforated plastically deformable sheet 3 according to a method of this invention. The method includes the steps of: (a) preparing a plastically deformable sheet 4; (b) preparing a drum-type screen mold 7 including a first screen element 71 and a second screen element 72 connected to and disposed above the first screen element 71, the first and second screen elements 71, 72 being respectively formed with a plurality of first and second screen holes 710, 720, each of the second screen holes 720 having a cross-section greater than those of the first screen holes 710, each of the second screen holes 720 spanning at least one of the first screen holes 710; (c) heating and softening the plastically deformable sheet 4 using a heater 8, laying the plastically deformable sheet 4 on the second screen element 72, and passing the plastically deformable sheet 4 over the screen mold 7 using a set of rollers 6; and (d) applying a negative pressure at one side of the first screen element 71 opposite to the softened plastically deformable sheet 4 using a vacuum device 9 in such a manner that the softened plastically deformable sheet 4 is pulled and ruptured at the first screen holes 710 so as to form the recesses 44 that respectively correspond to the second screen holes 720 and so as to form the capillaries 40 that respectively correspond to the first screen holes 710.

[0017] Fig. 7 illustrates another apparatus 300 that is similar to the apparatus 300 shown in Fig. 5, except that the screen mold 7 is elliptical in shape.

[0018] With the inclusion of the recesses 44 in the perforated plastically deformable sheet 3, the drawbacks as encountered in the prior art can be eliminated. Moreover, the recesses 44 permit the liquid that accumulated on the top surface 41 of the perforated plastically deformable sheet 3 to be quickly drained thereinto, thereby allowing a greater degree of dryness on the top surface 41 of the perforated plastically deformable sheet 3.

[0019] Each feature disclosed in this specification (which term includes the claims) and/or shown in the drawings may be incorporated in the invention independently of other disclosed and/or illustrated features.

[0020] Statements in this specification of the "objects of the invention" relate to preferred embodiments of the invention, but not necessarily to all embodiments of the invention falling within the claims.

[0021] The description of the invention with reference to the drawings is by way of example only.

[0022] The text of the abstract filed herewith is repeated here as part of the specification.

[0023] A perforated plastically deformable sheet (3) includes a plastically deformable sheet (4) with top and bottom surfaces (41, 42). The plastically deformable sheet (4) is formed with a plurality of recesses (44) and a plurality of capillaries (40), each of which extends from a respective one of the recesses (44). Each of the recesses (44) has a cross-section greater than that of the respective one of the capillaries (40).

## Claims

1. A perforated plastically deformable sheet (3) characterized by:

a plastically deformable sheet (4) having opposite top and bottom surfaces (41, 42) and formed with a plurality of spaced apart recesses (44) and a plurality of spaced apart capillary units that are vertically and respectively aligned with said recesses (44), each of said capillary units including at least one capillary (40) that has a cross-section less than that of the respective one of said recesses (44), each of said recesses (44) being indented from said top surface (41) toward said bottom surface (42) and being confined by a recess-confining wall (43) that has a peripheral surface (431) extending downwardly from said top surface (41) toward said bottom surface (42), and a bight surface (432) that extends laterally from said peripheral surface (431), said capillary (40) of each of said capillary units extending downwardly from said bight surface (432) of said recess-confining wall (43) of the respective one of said recesses (44) in a transverse direction relative to said bight surface (432) and having a top opening (401) adjoining the respective one of said recesses (44) and a bottom opening (402) opposite to said top opening (401) and spaced apart from said bottom surface (42) in a direction away from said top surface (41).

2. The perforated plastically deformable sheet (3) of Claim 1, characterized in that said capillary (40) of each of said capillary units is tapered from said top opening (401) toward said bottom opening (402).

3. The perforated plastically deformable sheet (3) of Claim 1, characterized in that said plastically deformable sheet (4) is made from a plastic material that is hydrophobic.

4. The perforated plastically deformable sheet (3) of Claim 1, characterized in that said plastically deformable sheet (4) includes a top layer (51) of a hydrophilic material and a bottom layer (52) of a hydrophobic material.

5. The perforated plastically deformable sheet (3) of Claim 1, characterized in that said plastically deformable sheet (4) is made from a non-woven fabric.

6. A method for making a perforated plastically deformable sheet (3), said method being characterized by the steps of:

(a) preparing a plastically deformable sheet (4);  
 (b) preparing a screen mold (7) including a first screen element (71) and a second screen element (72) connected to and disposed above said first screen element (71), said first and second screen elements (71, 72) being respectively formed with a plurality of first and second screen holes (710, 720), each of said second screen holes (720) having a cross-section greater than those of said first screen holes (710), each of said second screen holes (720) spanning at least one of said first screen holes (710);  
 (c) heating and softening said plastically deformable sheet (4) and laying said plastically deformable sheet (4) on said second screen element (72); and  
 (d) applying a negative pressure at one side of said first screen element (71) opposite to said softened plastically deformable sheet (4) in such a manner that said softened plastically deformable sheet (4) is pulled and ruptured at said first screen holes (710).

7. The method of Claim 6, characterized in that said screen mold (7) is formed by stacking said second screen element (72) over said first screen element (71).




FIG. 1  
PRIOR ART




FIG. 2  
PRIOR ART




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 25 8797

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 342 314 A (THOMPSON HUGH A ET AL) 3 August 1982 (1982-08-03) * column 4, line 41 - column 5, line 68 * ---	1,3,5-7	A61F13/15 D04H1/00 D04H3/00
A	US 4 323 069 A (AHR NICHOLAS A ET AL) 6 April 1982 (1982-04-06) * column 6, line 50 - column 7, line 52 * * column 9, line 18-32 * ---	1-3,6	
A	US 5 660 788 A (SCHETTLER MICHAEL J ET AL) 26 August 1997 (1997-08-26) * the whole document * ---	1,3,6	
A	EP 0 545 423 A (UNI CHARM CORP) 9 June 1993 (1993-06-09) * column 5, line 16 - column 6, line 51 * -----	1,3,6	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A61F D04H
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>21 November 2003</b>	Examiner <b>V Beurden-Hopkins, S</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons</p> <p>§: member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02) (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 8797

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-11-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4342314	A	03-08-1982	AT 6604 T	15-03-1984
			AU 541677 B2	17-01-1985
			AU 5611480 A	11-09-1980
			BR 8001307 A	04-11-1980
			CA 1140319 A1	01-02-1983
			CA 1155274 A2	18-10-1983
			DE 3066902 D1	19-04-1984
			EP 0018020 A1	29-10-1980
			ES 250912 U	01-01-1981
			ES 252982 Y	01-07-1982
			ES 8103977 A1	01-07-1981
			GR 67004 A1	18-05-1981
			HK 99288 A	16-12-1988
			IE 49278 B1	04-09-1985
			JP 1735236 C	17-02-1993
			JP 4008221 B	14-02-1992
			JP 55146738 A	15-11-1980
			JP 1937942 C	09-06-1995
			JP 3184541 A	12-08-1991
			JP 5028626 B	26-04-1993
			JP 1794258 C	14-10-1993
			JP 3198850 A	30-08-1991
			JP 5000066 B	05-01-1993
			MX 153289 A	11-09-1986
			US 4508256 A	02-04-1985
US 4323069	A	06-04-1982	AT 15591 T	15-10-1985
			CA 1150904 A1	02-08-1983
			DE 3172301 D1	24-10-1985
			EP 0040084 A2	18-11-1981
			JP 57089861 A	04-06-1982
US 5660788	A	26-08-1997	PH 17925 A	31-01-1985
			AT 189593 T	15-02-2000
			AU 701055 B2	21-01-1999
			AU 1096395 A	06-06-1995
			BR 9408104 A	05-08-1997
			CA 2175558 A1	26-05-1995
			DE 69422999 D1	16-03-2000
			DE 69422999 T2	17-08-2000
			EP 0729331 A1	04-09-1996
			ES 2141914 T3	01-04-2000
			GR 3032641 T3	30-06-2000
			HK 1012941 A1	03-11-2000
			JP 9505223 T	27-05-1997
			SG 55040 A1	21-12-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 8797

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-11-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5660788 A		WO 9513774 A1	26-05-1995
		US 5928210 A	27-07-1999
-----			
EP 0545423 A	09-06-1993	JP 2823402 B2	11-11-1998
		JP 5154175 A	22-06-1993
		AU 667850 B2	18-04-1996
		AU 2971292 A	10-06-1993
		CA 2084358 A1	05-06-1993
		CN 2149885 U	22-12-1993
		DE 69221439 D1	11-09-1997
		DE 69221439 T2	16-07-1998
		EP 0545423 A1	09-06-1993
		GB 2262042 A ,B	09-06-1993
		KR 119357 Y1	01-06-1998
		PH 30257 A	05-02-1997
		US 5387209 A	07-02-1995
-----			

EPO FORM P0463

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82